



1400 Series

Hot-Water Pressure Washers with 1725 RPM Motors

North America's #1 Manufacturer of High-Quality Cleaning Equipment

Electric / Belt Drive

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

Every Hotsy comes with 35 years of experience and rugged durability built-in

Model 1412SS with Natural Gas-Fired combustion chamber (Shown with optional hose reel)

7.5 HP Baldor, 1725 RPM electric motor is drip proof and comes with thermal overload protection and a manual reset

Stainless-steel coil skin provides extra durability to withstand the elements, resist corrosion and endure rough treatment

50-ft. length of high-pressure hose and hanger for ease in cleaning around a large area

Thermal rupture disk protects the machine and user from heat expansion

Adjustable upstream detergent injection provides high-pressure sudsing for better cleaning

Easy to understand **operating instructions** and warning labels

Water-resistant cabinet, electrical box and motor



Control panel includes adjustable temperature control, plus heavy-duty heater and pump motor switches

Convenient **hose reel bracket** (standard) accepts swivel or stationary reels

Built-in wand holder provides convenient storage



Hotsy-designed triplex belt-drive pump carries a 7-year limited warranty

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap. Tank is oversized to provide for long-running operating time (standard on oil-fired models)

Wheel kit and handle make for easy portability (standard on oil-fired models)

Heavy-duty fuel filter protects burner fuel pump

Model 1410SS: Oil Fired, 3.9 GPM @ 3000 PSI

Semi-pneumatic wheels eliminate the risk of flats

Float tank helps maintain constant water pressure and flow and helps prevent sediment from entering the machine's components...great for use in well-water environments and low-water situations



Insulated Hotsy Trigger Gun, rated to 3750 PSI. **36" insulated wand** with ergonomic, adjustable side handle

FEATURES

- 3.9 GPM @ 3000 PSI
- Oil Fired, LP or Natural Gas Fired
- 230V, 1PH; 208V, 230V or 460V, 3PH
- ETL-Certified to UL-1776 safety standards

www.Hotsy.com

Nothing Cleans Like A Hotsy!

1400 SERIES Hot-Water ELECTRIC Models with 1725 RPM Motors

■ Oil Fired, LP or Natural Gas-Fired ■ 3.9 GPM @ 3000 PSI ■ Hotsy Triplex Pump with 7-yr warranty ■ ETL-Certified for safety

Designed for tough, industrial cleaning.

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	PUMP RPM	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
1410SS	3.9	3000	7.5	1725	230/1	37	Oil	Hotsy Triplex	970	Belt	Std	50'	640
1411SS	3.9	3000	7.5	1725	230/1	34	LP	Hotsy Triplex	970	Belt	N/A	50'	610
1412SS	3.9	3000	7.5	1725	230/1	34	NG	Hotsy Triplex	970	Belt	N/A	50'	610
1420SS	3.9	3000	7.5	1725	230/3	25	Oil	Hotsy Triplex	970	Belt	Std	50'	640
1420SS-208	3.9	3000	7.5	1725	208/3	25	Oil	Hotsy Triplex	970	Belt	Std	50'	640
1421SS	3.9	3000	7.5	1725	230/3	24	LP	Hotsy Triplex	970	Belt	N/A	50'	605
1421SS-208	3.9	3000	7.5	1725	208/3	24	LP	Hotsy Triplex	970	Belt	N/A	50'	605
1422SS	3.9	3000	7.5	1725	230/3	24	NG	Hotsy Triplex	970	Belt	N/A	50'	605
1422SS-208	3.9	3000	7.5	1725	208/3	24	NG	Hotsy Triplex	970	Belt	N/A	50'	605
1423SS	3.9	3000	7.5	1725	460/3	14	Oil	Hotsy Triplex	970	Belt	Std	50'	640
1424SS	3.9	3000	7.5	1725	460/3	12	LP	Hotsy Triplex	970	Belt	N/A	50'	605
1425SS	3.9	3000	7.5	1725	460/3	12	NG	Hotsy Triplex	970	Belt	N/A	50'	605

Dimensions: 45"l x 18"w x 48"h



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's

exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 130 local Sales & Service Distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 97-0451 Effective 2/05 Specifications & product descriptions subject to change without notice. ©2005 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.

OPTIONS for 1400 SERIES with 1725 RPM Motors

- **Primary & Additional Remote Stations** provide easy operation in wash bays or multiple stations
- **Shutdown Timer** allows automatic machine shutdown
- **Auto Start/Stop** provides preset & adjustable on/off machine operation
- **8" Natural Gas or LP Gas Fired Draft Diverters** prevent backdrafts; keeps cold air out & prevents water from running down vent pipes
- **8" Oil-Fired Draft Dampener; barometric;** prevent back drafts; keeps cold air out & prevents water from running down vent pipes

Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning




Remote control box allows pressure washer to be located in one room; controls and wands in other rooms

Telescoping wands extend to 24' to reach high places without scaffolding



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping



Foamers increase dwell time on vertical surfaces, such as tractor trailers, walls and crates